




Product Specification Sheet


制图

审核


批准




产品型号: RY-15G



产品型号: RY-20G



产品型号: RY-25G



P
C PCB
B Plate
板 hole
孔 diagram
位
图

变更说明 Change description	更改人 Change person	更改日期 change date	备注 remarks
/	/	/	/
/	/	/	/

性能参数 (表 2.1)	
Performance parameters (Table 2.1)	
安装方式 Installation method	PCB板焊接 PCB board soldering
外观材料 Appearance material	底座 base
	接触片 contact piece
插拔力 Insertion and extraction force	插座与连接器间：首次插入力 $\geq 25N$ ， $\leq 45N$ ；首次拔出力 $\geq 20N$ ， $\leq 50N$ Between socket and relay: initial insertion force $\geq 25N$, $\leq 45N$; First extraction force $\geq 20N$, $\leq 50N$
插拔次数 Number of insertions and removals	≥ 1 万次(插座与连接器之间的插拔次数) times (number of insertions and removals between sockets and relays)
工作环境温度 Working environment temperature	-40℃~+80℃，非真空状态，不结冰情况下 -40 ℃~+80 ℃, under non vacuum and non icing conditions
工作环境湿度 Working environment humidity	35%~85%RH
贮存环境温度 Storage environment temperature	包装完好情况下，-40℃~+55℃ Under intact packaging, -40 ℃ to +55 ℃
贮存环境湿度 Storage environment humidity	包装完好情况下，45%~90%RH When the packaging is intact, 45-90% RH
额定参数 Rated parameters	16A 250VAC
接触电阻 contact resistance	$\leq 50m\Omega$
绝缘电阻 Insulation resistance	$\geq 1000M\Omega$ (500VDC)
抗电强度 (工频耐压) Dielectric strength (50Hz voltage)	相邻端子之间：2000VAC, 50HZ, 1min(漏电流1mA) Between adjacent terminals: 2000VAC, 50HZ, 1min (leakage current 1mA)

性能参数 (表 2.2)	
Performance parameters (Table 2.2)	
耐振性 Vibration resistance	XYZ 三向, 60Hz, 振幅 2mm, 10 小时 (每 2 小时观察记录) XYZ three-way, 60Hz, amplitude 2mm, 10 hours (observe and record every 2 hours)
产品防跌落 Product drop fall	底座垂直跌落 1 米, 3 次, 能正常工作 The base has dropped vertically by 1 meter for 3 times and can work normally
包装跌落 Packaging falling	600mm 高度连续跌落 4 次, 产品无损坏 4 consecutive drops from a height of 600mm without any damage to the product
耐冲击性 Impact resistance	各部位能承受冲击力 10g, 能正常工作 Each part can withstand an impact force of 10g and work normally
温升试验 Temperature rise test	按 GB/T 11404.8, 5 标准中 8.3.3.3 条款 (恒温 25℃, 持续通电 60min, 所有触点满载) According to clause 8.3.3.3 of GB/T 11404.8, 5 standard, continuous power-on for 60 minutes, all contacts are fully loaded, and the temperature difference before and after the 1-hour test interval does not exceed 50C
盐雾试验 Salt spray test	24h, 1 个周期, (参考 GB/T 2423.18-2012) 24 hours, 1 cycle, (refer to GB/T 2423.18-2012)
低温试验 Low temperature test	-40℃, 96h, 接触电阻 ≤200mΩ -40℃, 96 hours, contact resistance ≤ 200m Ω
高温试验 High temperature test	80℃, 96h, 接触电阻 ≤200mΩ 80℃, 96 hours, contact resistance ≤ 200m Ω
高低温冲击试验 High/Low temperature impact test	-40~+85℃, 85%RH, 40min/循环, 50 个循环, 接触电阻 ≤200mΩ -40~+85℃, 85% RH, 40min/cycle, 50 cycles, contact resistance ≤ 200m Ω
图纸未注一般公差	按 GB/T 1804-m 标准执行 Execute according to GB/T 1804-m standard



RY-ELE®

浙江荣越电气有限公司
Zhejiang Rongyue Electric Co., Ltd

产品名称 Product Name	继电器底座 Relay base
产品型号 Product drawing number	14F-1Z-A1