产品规格书
Product Specification Sheet

变更说明	更改人	更改日期	备注
/	/	/	/
/	/	/	/





		性能参数 （表2.1） Relay performance parameters (Table 2.1)
安装方式 Installation method		适配继电器、卡扣式安装 Adapted relay and snap on installation
底座材料 Base Material	外壳 Housing	PA6（RoHS）+GF20% V0级阻燃 PA6 (RoHS)+GF20% V0 flame retardant
	盖板 Cover Plate	PA6（RoHS）+GF20% V0级阻燃 PA6 (RoHS)+GF20% V0 flame retardant
	卡扣 Buckle	POM（RoHS）
	连接片 Connecting piece	高精黄铜带H62Y，厚0.3mm,表面镀铜锡 High precision brass strip H62Y, thickness 0.3mm, surface plated with copper and tin
	螺钉 Screw	材料10B21,表面镀镍，M3螺钉 Material 10B21, surface nickel plated, M3 screw
	螺钉垫片 Screw washer	不锈铁 Stainless iron
接线形式 Wiring form		螺钉接线，使用0.5-1.5mm²国标线（适配相应跨接条） Screw wiring, using 0.5-1.5mm² National standard line (adapted to corresponding jumper bars)
拧紧扭矩 Screw Torque		0.6N.m扭矩力作用下螺钉无滑牙，无断裂现象 Under the action of a torque force of 0.6N.m, there is no slippage or fracture of the screw
插拔力 Insertion and extraction force		首次插入力≥25N，≤75N；首次拔出力≥20N，≤70N First insertion force ≥ 25N, ≤ 75N; First extraction force ≥ 20N, ≤ 70N
插拔次数 Insertion and removal times		≥1000次(插座与继电器之间的插拔次数) ≥ 1000 times (insertion and extraction times between sockets and relays)
工作环境温度 Ambient Temperature		-40℃～+80℃，非真空状态、不结冰情况下 -40 ℃~+80 ℃, in non vacuum and non icing conditions
工作环境湿度 Working environment humidity		35～85%RH
贮存环境温度 Storage environment temperature		包装完好情况下，-40℃～+55℃ Under intact packaging, -40 ℃ to+55 ℃
贮存环境湿度 Storage environment humidity		包装完好情况下，45～90%RH 45~90% RH with intact packaging
额定参数 Rated		12A 300VAC/24VDC
接触电阻 Contact Resistance		≤100mΩ
绝缘电阻 Insulation Resistance		≥1000MΩ(500VDC)
抗电强度（工频耐压） Dielectric strength		相邻端子之间：1800VAC，50HZ，1min(漏电流1mA) Between adjacent terminals: 1800VAC, 50HZ, 1min (leakage current 1mA)

性能参数 （表2.2） Relay performance parameters (Table 2.2)	
耐振性 resistance to vibration	XYZ三向，60HZ,振幅2mm ,10小时(每2小时观察记录) XYZ three way, 60HZ, amplitude 2mm, 10 hours (observe and record every 2 hours)
产品防跌落 Product drop prevention	底座竖直跌落1米，3次，能正常工作 The shell end drops vertically for 1 meter, 3 times, and can work normally
包装跌落 Packaging drop	600mm高度连续跌落4次，产品无损坏 4 consecutive drops from a height of 600mm, with no damage to the product
耐冲击性 Impact resistance	各部位能承受冲击力10g，能正常工作 Each part can withstand an impact force of 10g and work normally
温升试验 Temperature rise test	按GB/T14048.5标准中8.3.3.3条款(恒温25℃，持续通电60Min,所有触点满负载, 1个小时测试间隔内,前后温差不超过55K) According to clause 8.3.3.3 of GB/T14048.5 standard (constant temperature of 25 ℃, continuous power on for 60 minutes, full load on all contacts, within one hour of testing interval, the temperature difference between the front and rear should not exceed 55K)
低温试验 Low temperature test	-40℃，96h，接触电阻≤200mΩ -40 ℃, 96h, contact resistance ≤ 200m Ω
高温试验 High Temperature Test	80℃，96h，接触电阻≤200mΩ 80 ℃, 96h, contact resistance ≤ 200m Ω
高低温冲击试验 High and low temperature impact test	-40～+85℃，85%RH，40min/循环，50个循环，接触电阻≤200mΩ -40~+85 ℃, 85% RH, 40min/cycle, 50 cycles, contact resistance ≤ 200m Ω
产品认证 Product Certification	CE RoHS
图纸未注一般公差 General tolerances not indicated on the drawings	按GB/T 1804-m 标准执行。 Follow the GB/T 1804-m standard.
产品包装数量 Product packaging quantity	500只/箱 500 pieces/box
包装盒尺寸 **Packaging box size**	44.5cm*32cm*39cm
单只产品净重(约) Net weight of a single product (approximately)	33.8g

温馨提示：请勿带电操作
Kind reminder: Do not operate with electricity

内部接线原理图
Internal wiring schematic





轴测图
Isometric Drawing

所有尺寸均以mm为单位
不能从图纸上测绘尺寸
All dimensions are in millimeters
Unable to measure dimensions from drawings

比例 Scale	1:1
图幅 Size	A4
页码 Page	1/1

制图 Drawing	旭淼	日期 Date	2022-8-20
审核 Audit	何军	日期 Date	2022-8-20
批准 Approval	前锋	日期 Date	2022-8-20

RY-ELE®
温州瑞繁电器有限公司
Wenzhou Ruifan Electrical Co., Ltd.

产品名称 Product Name	继电器底座 Relay base
产品型号 Product drawing number	RTF08A2